

SAURO LED

ROUND BOLLARD- CLASSIC



Bollard range in classic style made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Supplied with TÜV-CB certified, long-life, efficient and **Kelvin settable GX53 LED lamp included**. Uniform light distribution for a safer and more enjoyable night atmosphere. Insulation class II, protection rating IP55.

*Gamma di bollard in stile classico, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Fornita con **inclusa lampadina a LED GX53 con Kelvin impostabile** certificata TÜV-CB, di lunga durata ed elevata efficienza. Uniforme distribuzione della luce per un'atmosfera notturna sicura e gradevole. Classe di isolamento II, grado di protezione IP55.*

D15.555.D1KCRB



CCT SETTABLE



SDCM <6

3000 K

4000 K

6500 K



MADE IN ITALY

SAURO LED COMPONENTS

IP55



CAP made of shockproof resin material, locked to the diffuser and equipped with GX53 led lamp. To be removed for relamping by the supplied hexagonal key for locking screws.

***CALOTTA** fissata al diffusore, realizzata in resina antiurto e completa di lampadina led GX53. Rimovibile tramite vite di sicurezza per permettere il cambio della lampadina.*

DISK made of UV-rays stabilized PMMA to spread the light and to get a lower dazzle.

***DISCO** in polimetilmetacrilato (PMMA) per diffondere la luce e ridurre l'abbagliamento.*

DIFFUSER of UV stabilized polymethylmethacrylate (PMMA) resistant to yellowing process due to sun rays, available in clear or opal colour.

***DIFFUSORE** in polimetilmetacrilato (PMMA) resistente all'ingiallimento ed ai raggi UV, disponibile in colore trasparente o opale.*

White **REFLECTOR** with conical shape made of shockproof resin material.

***RIFLETTORE** bianco a forma conica, realizzato in resina antiurto.*

CONNECTION RING made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

***GHIERA** di raccordo realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.*

SAURO LED

Ø150



Dimensions

Diameter: Ø150 mm

Height: 500/800/1100 mm

Moulded colours:

Black White
Grey

Painted colours:

Antique green Antique bronze

Diffuser PMMA:

Clear Opal

LED LAMPS



Comply with: EU2019/2015
EU2019/2020
Technical details on page 668.

GX53 LED

100 - 240 V



Bollard supplied as standard with TÜV-CB certified, long-life, efficient and Kelvin settable GX53 LED lamp included. Quick and easy lamp replacement for a very simple maintenance after installation.

LAMP	POWER	LUMINOUS FLUX (Φ TOTAL) UP TO	COLOUR TEMP.	*ADD. SUFFIX
GX53 LED	10 W	1290 lm	6500 K 4000 K 3000 K	.D1K



- **COST SAVING:** long-life and efficient LED light sources.
- **BUILT-IN DRIVER:** quick and easy lamp replacement.
- **GREAT FLEXIBILITY:** GX53 standard lamp holder.
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments.
- **SUITABLE FOR OUTDOOR USE:** driver fully protected against heat and humidity by silicone paste.

CCT SETTABLE LED LAMP



CCT switch settable in three different positions, to select the desired Kelvin temperature (3000K/4000K/6500K) and get a customized ambience.

PHOTOMETRIC DATA SAMPLE



SAURO 1100 GX53 LED-clear 10W.

Sauro height 1,1 mt
Area: 6x6 mt - average
11 lux

The photometric data for all the versions are available upon request or on our website.



SAURO LED

ROUND BOLLARD- CLASSIC



D15.554.D1KCRB



D15.553.D1KCRB



D15.505.D1KCRB

MADE IN ITALY

SAURO 1100 LED
10W D15.555.D1KCRB

CCT SETTABLE GX53 LED LAMP INCLUDED
3000K/4000K/6500K

Pcs 1
Kg 4,2
mc 0,068

SAURO 800 LED
10W D15.554.D1KCRB

CCT SETTABLE GX53 LED LAMP INCLUDED
3000K/4000K/6500K

Pcs 1
Kg 3,4
mc 0,05

MIRELLA LED
10W D15.505.D1KCRB

CCT SETTABLE GX53 LED LAMP INCLUDED
3000K/4000K/6500K

Pcs 1
Kg 2,7
mc 0,032

SAURO 500 LED
10W D15.553.D1KCRB

CCT SETTABLE GX53 LED LAMP INCLUDED
3000K/4000K/6500K

Pcs 1
Kg 2
mc 0,032