

SANDRO

MEDIUM SIZE

fumagalli
since 1973

E27 hexagonal lantern in modern revival style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Modular construction suitable for post top, hanging and wall installation. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP55.

*Lanterna esagonale E27 in stile revival moderno, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a palo, a sospensione o a parete. Fornita anche completa di **lampadine LED** adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*



6,5W 800 lm	8,5W 920 lm	11W 1200 lm
2700 K	2700 K	4000 K 6500 K
+80°C -30°	90% HUMIDITY	VOLTAGE SURGE RESISTANT

INDOOR & OUTDOOR USE

H24.240.V1K



SANDRO - LANTERN COMPONENTS

IP55



Decorative **PINNACLE** provided with silicone rubber gasket to be mounted on the roof top for post installation or on the lantern base for hanging installation.

***PINNACOLO** decorativo completo di guarnizione in gomma siliconica applicabile alla sommità del tetto (montaggio a palo) o sulla base della gabbia (montaggio a sospensione).*

Lantern **ROOF** made of shockproof resin material, UV rays stabilized and supplied with E27 lampholder. Easy opening for relamping and maintenance.

***TETTO** realizzato in resina antiurto, stabilizzata ai raggi UV, fornito completo di portalampada E27. Facilmente rimovibile per manutenzione e cambio lampadina.*

DIFFUSER made of UV stabilized polymethylmethacrylate (PMMA) resistant to yellowing process due to sun rays, available in clear or opal color and provided with recess for power cable supply. Made of one piece only and closed at the bottom to ensure high protection against external agents (IP 55).

***DIFFUSORE** in polimetilmetacrilato (PMMA) resistente al processo di ingiallimento dovuto ai raggi solari, disponibile in colore trasparente od opale e provvisto di scanalatura per il passaggio del cavo di alimentazione. Realizzato in un pezzo unico e con fondo chiuso per garantire un alto livello di protezione contro gli agenti esterni (IP 55).*

CAGE made of shockproof resin material, UV-rays stabilized, rust and corrosion-free.

***GABBIA** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.*

SANDRO

H24.000 *



Dimensions and weight

Height: 310 mm
Width: 240 mm
Depth: 230 mm
Weight: 1,1 Kg

Moulded colours:

Black White
Grey

Diffuser PMMA:

Clear Opal

E27 FILAMENT



- perfect **MATCHING WITH DECORATIVE LANTERNS.**
- **SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- **360°OMNIDIRECTIONAL LIGHT.**
- **HIGH EFFICIENCY:** 90% ENERGY SAVING.

E27 CCT SET



- **A60 CCT SETTABLE:** 2700K/4000K/6500K.
- **SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- **EYE COMFORT** opal glass.
- **HIGH EFFICIENCY:** >85% ENERGY SAVING.

100 - 240 V


suitable lamps: CFL-LED max 160 mm		E27 lampholder only		.E27
LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.	
 FILAMENT LED E27	6,5W	800 lm	2700 K	.F1R
 CCT SET LED E27	8,5 W	920 lm	6500 K 4000 K 2700 K	.V1K
 CCT SET LED E27	11 W	1200 lm	6500 K 4000 K 2700 K	.T1K
 6,5W filament		=	60W incandescent	
 8,5W CCT				
 11W CCT		=	75W incandescent	
SAVE up to 89%				

LED LAMPS




Comply with: EU2019/2015
EU2019/2020
Technical details on page 668.

CCT SETTABLE LED LAMP



CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambiance.

PHOTOMETRIC DATA SAMPLE



SANDRO lantern clear with
Fumagalli Led Lamp CCT set 8,5W.

POST height 2mt
6x6mt area: average 6 lux

The photometric data for all the versions are available upon request or on our website.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

SANDRO

MEDIUM SIZE




H24.306.V1K



H24.116.V1K



H24.242.V1K




H24.125.V1K

NARDO/SANDRO

E27 lampholder	H24.240.E27
6,5W filament	H24.240.F1R
8,5W CCT set	H24.240.V1K
11W CCT set	H24.240.T1K


Pcs 12
Kg 15,7
mc 0,216



MIDIDISMA/SANDRO

E27 lampholder	H24.116.E27
6,5W filament	H24.116.F1R
8,5W CCT set	H24.116.V1K
11W CCT set	H24.116.T1K


Pcs 12
Kg 15,6
mc 0,216



SICAR/SANDRO


E27 lampholder	H24.125.E27
6,5W filament	H24.125.F1R
8,5W CCT set	H24.125.V1K
11W CCT set	H24.125.T1K

Pcs 12
Kg 17,5
mc 0,216



SANDRO
H24.000


Pcs 1
Kg 1,1
mc 0,018



GIAFFA/SANDRO resin

E27 lampholder	H24.242.E27
6,5W filament	H24.242.F1R
8,5W CCT set	H24.242.V1K
11W CCT set	H24.242.T1K


Pcs 1
Kg 2,1
mc 0,07



DANILO/SANDRO

E27 lampholder	H24.305.E27
6,5W filament	H24.305.F1R
8,5W CCT set	H24.305.V1K
11W CCT set	H24.305.T1K


Pcs 1
Kg 9,1
mc 0,125



DINO/SANDRO






E27 lampholder	H24.306.E27
6,5W filament	H24.306.F1R
8,5W CCT set	H24.306.V1K
11W CCT set	H24.306.T1K

Pcs 1
Kg 10,4
mc 0,143



SANDRO
MEDIUM SIZE





ROBY

SMALL SIZE



E27 square lantern in modern revival style, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Modular construction suitable for post top, hanging and wall installation. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP55.

*Lanterna quadra E27 in stile revival moderno, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Idonea per il montaggio a palo, a sospensione o a parete. Fornita anche completa di **lampadine LED** adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*

6,5W 800 lm	8,5W 920 lm	11W 1200 lm
2700 K	2700 K	4000 K 6500 K
+80°C -30°	90% HUMIDITY	VOLTAGE SURGE RESISTANT

INDOOR & OUTDOOR USE



T20.240.V1K



MADE IN ITALY