

GIULIO

MEDIUM SIZE



Half lantern in modern revival style with E27 lampholder, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Supplied as optional with TÜV-CB certified, long-life and efficient **LED lamps** suitable for outdoor use. Insulation class II, protection rating IP 55.



GIULIO
M24.000

S M25.000
SMART PACK

*Mezza lanterna in stile revival moderno con portalampada E27, realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Fornita anche completa di **lampadine LED** adatte ad uso in ambiente esterno, certificate TÜV-CB, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP55.*

6,5W 800 lm	8,5W 920 lm	11W 1200 lm
2700 K	2700 K	4000 K 6500 K
+80°C -30°	90% HUMIDITY	VOLTAGE SURGE RESISTANT
INDOOR & OUTDOOR USE		



M24.000.T1K

RECYCLABLE	ANTI-SHOCK	TEMPERATURE	FILAMENT LED	WALL

MADE IN ITALY

GIULIO - LANTERN COMPONENTS

IP55



CAGE made of shockproof resin material, UV rays stabilized, rust and corrosion-free.

***GABBIA** realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione.*



DIFFUSER made of UV stabilized polymethylmethacrylate (PMMA), one piece only closed on the top to ensure high protection against external agents. Available in clear or opal colour.

***DIFFUSORE** in polimetilmetacrilato (PMMA), realizzato in un unico pezzo chiuso in cima per garantire un alto livello di protezione contro gli agenti esterni. Disponibile in colore trasparente od opale.*



WALL PLATE made of shockproof white resin reflective material, UV rays stabilized, rust and corrosion-free. Provided with double cable entry and supplied complete with E27 lampholder.

***BASE A MURO** realizzata in resina antiurto in colore bianco riflettente, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Provvista di doppia entrata per il cavo elettrico e fornita completa di portalampada E27.*

GIULIO

M24.000



Dimensions and weight

Height: 375 mm
Width: 265 mm
Depth: 140 mm
Weight: 1,1 Kg

Moulded colours:

Black White
Grey

Diffuser PMMA:

Clear Opal

E27 FILAMENT



E27 CCT SET



100 - 240 V



*ADD. SUFFIX

suitable lamps: CFL-LED max 160 mm		E27 lampholder only		.E27
LAMP	POWER	LUMINOUS FLUX UP TO	COLOUR TEMP.	
 FILAMENT LED E27	6,5W	800 lm	2700 K	.F1R
 CCT SET LED E27	8,5 W	920 lm	6500 K 4000 K 2700 K	.V1K
 CCT SET LED E27	11 W	1200 lm	6500 K 4000 K 2700 K	.T1K
 6,5W filament		=	60W incandescent	
 8,5W CCT		=	75W incandescent	
 11W CCT		=		
SAVE up to 89%				

- perfect **MATCHING WITH DECORATIVE LANTERNS.**
- SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- 360°OMNIDIRECTIONAL LIGHT.**
- HIGH EFFICIENCY:** 90% ENERGY SAVING.

- A60 CCT SETTABLE:** 2700K/4000K/6500K.
- SUITABLE FOR OUTDOOR USE:** 100-240V driver.
- EYE COMFORT** opal glass.
- HIGH EFFICIENCY:** >85% ENERGY SAVING.

PHOTOMETRIC DATA SAMPLE



GIULIO lantern clear with Fumagalli Filament Led Lamp 6,5W.

height wall mounting: 2mt
6x6mt area: average 4 lux


The photometric data for all the versions are available upon request or on our website.

LED LAMPS



Comply with: EU2019/2015
EU2019/2020
Technical details on page 668.

CCT SETTABLE LED LAMP




CCT switch settable in three different positions, to select the desired Kelvin temperature (2700K/4000K/6500K) and get a customized ambiance.

* ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

HALF LANTERNS

GARDEN REVIVAL



FABIO	
E27 lampholder	M20.000.E27
6,5W filament	M20.000.F1R
8,5W CCT set	M20.000.V1K
Pcs 18 Kg 15,4 mc 0,172	
	

GIULIO	
E27 lampholder	M24.000.E27
6,5W filament	M24.000.F1R
8,5W CCT set	M24.000.V1K
11W CCT set	M24.000.T1K
Pcs 12 Kg 13,6 mc 0,20	
